

AstroScope™






for Nikon and Canon dSLR Cameras

NIGHT VISION ADAPTER

AstroScope™ is an advanced night vision module that incorporates a state-of-the-art image intensifier and high quality optics to transform dark scenes into bright, high resolution images and videos. The AstroScope™ is specifically designed to be used with a Nikon or Canon digital camera. The modules mount seamlessly between the camera body and lens. AstroScope™ delivers seamless integration with the camera body and requires no additional batteries. When you need to get the shot, AstroScope™ delivers.

FOR EXPORT ONLY

ENHANCE YOUR VISIBILITY IN LOW LIGHT / NO LIGHT

-  **POWERED BY CAMERA BATTERY**
-  **SEAMLESS ELECTRONIC INTEGRATION**
-  **PRESERVES CAMERA SETTINGS & LENS CONTROL**
-  **NO ADDITIONAL CABLES OR CHARGING**
-  **WHITE PHOSPHOR OR GREEN PHOSPHOR OPTIONS AVAILABLE**

SURVEILLANCE

LEISURE

DEFENSE



●● CONVERT YOUR dSLR CAMERA INTO A HIGH-PERFORMANCE NIGHT VISION SYSTEM ●●



Tactical Imaging



Law Enforcement



Surveillance



Wildlife Management


AstroScope Modular Configurations

At the heart of the AstroScope is a Central Intensifier Unit that, with additional components, can be reconfigured as shown below.


Canon or Nikon SLR Camera



Without AstroScope™



With AstroScope™



Both shots were taken using the same camera settings

Shutter Speed: 1/40; No Flash; Lens Aperture: F/5; Focal Length: 52 mm; ISO: 800; Exposure Comp: 0

Standard Lead Time: 4-6 Weeks, Call for Pricing.

Export of this product is controlled by the US State Department. Prior authorization is required for re-export or transfer.

LYNRED HEADQUARTERS
Avenue de la Vauve - CS 20018
91127 Palaiseau - France
Phone +33 (0)1 60 92 18 30
info@lynred.com

DEVELOPMENT AND PRODUCTION CENTER
Actipole - CS 10021 - 364, route de Valence
38113 Veurey-Voroize - France
Phone +33 (0)4 76 28 77 00
info@lynred.com

LYNRED ASIA PACIFIC PTE LTD
5 Shenton way,
#22-04 UIC Building
068808 Singapore
info@lynred.com

LYNRED USA
373 US Highway 46W
Fairfield, NJ 07004, USA
Phone +1 973.882.0211
info@lynred-usa.com

GENERAL SPECIFICATIONS

Intensifier	Generation 3 mil-spec, 18 mm GaAs, MCP
Lifetime	>12,000 hours continuous use
Power Requirements	<300mW (<50mA typical)
Operating Temperature	-20° to 50° C
Storage Temperature	-40° to 80° C
Water Resistance	Splash Proof
Warranty	1 Year, workmanship and materials

FEATURED PRODUCTS

PRODUCT DESCRIPTION	PART #	CANON/NIKON	BODY TYPE	PHOSPHOR	GAIN
9350EOS-PV (Adapter Only)	915005	EOS	dSLR	NA	VARIABLE
9350EOS-P (Adapter Only)	914550	EOS	dSLR	NA	STANDARD
Canon Full Frame Adapter	914991	EOS	dSLR	NA	FF ADAPTER
9350NIKSPV (Adapter Only)	914992	NIK	dSLR	NA	VARIABLE
9350NIKSP (Adapter Only)	914541	NIK	dSLR	NA	STANDARD
Nikon Full Frame Adapter	914990	NIK	dSLR	NA	FF ADAPTER
9350 CIU-3VF-1600-GP	914982	CIU	dSLR	GREEN	VARIABLE
9350 CIU-3VF-1600-WP	915796	CIU	dSLR	WHITE	VARIABLE
9350 CIU-3F-1600-GP	914399	CIU	dSLR	GREEN	STANDARD
9350 CIU-3F-1600-WP	915796	CIU	dSLR	WHITE	STANDARD
9350 CIU-3VF-1800-GP	915514	CIU	dSLR	GREEN	VARIABLE
9350 CIU-3VF-1800-WP	915800	CIU	dSLR	WHITE	VARIABLE
9350 CIU-3F-1800-GP	915513	CIU	dSLR	GREEN	STANDARD
9350 CIU-3F-1800-WP	915814	CIU	dSLR	WHITE	STANDARD
9350 CIU-3VF-2000-GP	915666	CIU	dSLR	GREEN	VARIABLE
9350 CIU-3VF-2000-WP	915808	CIU	dSLR	WHITE	VARIABLE
9350 CIU-3F-2000-GP	915665	CIU	dSLR	GREEN	STANDARD
9350 CIU-3F-2000-WP	915807	CIU	dSLR	WHITE	STANDARD
9350 CIU-3VF-2200-GP	915659	CIU	dSLR	GREEN	VARIABLE
9350 CIU-3VF-2200-WP	915736	CIU	dSLR	WHITE	VARIABLE
9350 CIU-3F-2200-GP	915660	CIU	dSLR	GREEN	STANDARD
9350 CIU-3F-2200-WP	915735	CIU	dSLR	WHITE	STANDARD

Additional parts upon request.